

Cable Ties

Stainless steel cable ties

- Suitable when required ability to withstand harsh conditions and extremely high temperatures
- Suitable for a wide range of applications such as tightening and binding of cables, tightening of pipes, reinforcement of buildings, security and more.
- Using the product shortens the tightening and connection time significantly.
- The product is disposable and not reusable
- Note: After tightening the product, it cannot be released except by cutting the cable tie with a cutter
- The product is made of corrosion-resistant stainless steel
 - Material that is especially resistant to harsh weather conditions, humidity, and areas with a particularly high temperature



Lorem ipsum

ISO 9001
ISO 14001



ABS

ITEMS:

Catalog No	Model	Length (mm)	Width (mm)	Diameter (mm)	Tensile Strength (KGS)	Quantity in bag	Quantity in carton (bag)
MCT3330100	MST-100	100	4.6	22	46	100	100
MCT3350152	MST-152	152	4.6	35	46	100	100
MCT3370152	MTL-152	152	7.9	35	80	100	50
MCT3390152	MTB-152	152	12	35	120	100	50
MCT3410175	MST-175	175	4.6	40	46	100	100
MCT3430175	MTL-175	175	7.9	40	80	100	50
MCT3450175	MTB-175	175	12	40	120	100	40
MCT3470200	MST-200	200	4.6	50	46	100	100
MCT3490200	MTL-200	200	7.9	50	80	100	50
MCT3510200	MTB-200	200	12	50	120	100	40
MCT3530250	MST-250	250	4.6	65	46	100	50
MCT3550250	MTL-250	250	7.9	65	80	100	50
MCT3570250	MTB-250	250	12	65	120	100	40
MCT3590300	MST-300	300	4.6	80	46	100	50
MCT3610300	MTL-300	300	7.9	80	80	100	40
MCT3630300	MTB-300	300	12	80	120	100	30
MCT3650360	MST-360	360	4.6	95	46	100	50
MCT3670360	MTL-360	360	7.9	95	80	100	40
MCT3690360	MTB-360	360	12	95	120	100	20
MCT3710400	MST-400	400	4.6	105	46	100	50
MCT3730400	MTL-400	400	7.9	105	80	100	40
MCT3750400	MTB-400	400	12	105	120	100	20
MCT3770520	MST-520	520	4.6	150	46	100	50
MCT3790520	MTL-520	520	7.9	150	80	100	30
MCT3810520	MTB-520	520	12	150	120	100	20



Catalog No	Model	Length (mm)	Width (mm)	Diameter (mm)	Tensile Strength (KGS)	Quantity in bag	Quantity in carton (bag)
MCT3830600	MST-600	600	4.6	180	46	100	40
MCT3850600	MTL-600	600	7.9	180	80	100	30
MCT3870600	MTB-600	600	12	180	120	100	20
MCT3890680	MST-680	680	4.6	195	46	100	40
MCT3910680	MTL-680	680	7.9	195	80	100	30
MCT3930680	MTB-680	680	12	195	120	100	20
MCT3950840	MST-840	840	4.6	250	46	100	30
MCT3970840	MTL-840	840	7.9	250	80	100	20
MCT3990840	MTB-840	840	12	250	120	100	20
MCT4011050	MST-1050	1050	4.6	285	46	100	30
MCT4031050	MTL-1050	1050	7.9	285	80	100	15
MCT4051050	MTB-1050	1050	12	285	120	100	10
MCT3340100	HST-100	100	4.6	22	46	100	100
MCT3360152	HST-152	152	4.6	35	46	100	100
MCT3380152	HTL-152	152	7.9	35	80	100	50
MCT3400152	HTB-152	152	12	35	120	100	50
MCT3420175	HST-175	175	4.6	40	46	100	100
MCT3440175	HTL-175	175	7.9	40	80	100	50
MCT3460175	HTB-175	175	12	40	120	100	40
MCT3480200	HST-200	200	4.6	50	46	100	100
MCT3500200	HTL-200	200	7.9	50	80	100	50
MCT3520200	HTB-200	200	12	50	120	100	40
MCT3540250	HST-250	250	4.6	65	46	100	50
MCT3560250	HTL-250	250	7.9	65	80	100	50
MCT3580250	HTB-250	250	12	65	120	100	40
MCT3600300	HST-300	300	4.6	80	46	100	50
MCT3620300	HTL-300	300	7.9	80	80	100	40
MCT3640300	HTB-300	300	12	80	120	100	30
MCT3660360	HST-360	360	4.6	95	46	100	50
MCT3680360	HTL-360	360	7.9	95	80	100	40
MCT3700360	HTB-360	360	12	95	120	100	20
MCT3720400	HST-400	400	4.6	105	46	100	50
MCT3740400	HTL-400	400	7.9	105	80	100	40
MCT3760400	HTB-400	400	12	105	120	100	20
MCT3780520	HST-520	520	4.6	150	46	100	50
MCT3800520	HTL-520	520	7.9	150	80	100	30
MCT3820520	HTB-520	520	12	150	120	100	20
MCT3840600	HST-600	600	4.6	180	46	100	40
MCT3860600	HTL-600	600	7.9	180	80	100	30
MCT3880600	HTB-600	600	12	180	120	100	20
MCT3900680	HST-680	680	4.6	195	46	100	40
MCT3920680	HTL-680	680	7.9	195	80	100	30
MCT3940680	HTB-680	680	12	195	120	100	20
MCT3960840	HST-840	840	4.6	250	46	100	30



Catalog No	Model	Length (mm)	Width (mm)	Diameter (mm)	Tensile Strength (KGS)	Quantity in bag	Quantity in carton (bag)
MCT3980840	HTL-840	840	7.9	250	80	100	20
MCT4000840	HTB-840	840	12	250	120	100	20
MCT4021050	HST-1050	1050	4.6	285	46	100	30
MCT4041050	HTL-1050	1050	7.9	285	80	100	15
MCT4061050	HTB-1050	1050	12	285	120	100	10
MCT4070152	MFO-152	152	12	0.4	32	100	25
MCT4080152	MFL-152	152	12	0.4	32	100	20
MCT4090200	MFO-200	200	12	0.4	47	100	20
MCT4100200	MFO-200L	200	15	0.4	47	100	15
MCT4110200	MFL-200	200	12	0.4	47	100	20
MCT4120200	MFL-200L	200	15	0.4	47	100	15
MCT4130300	MFO-300	300	12	0.4	77	100	20
MCT4140300	MFO-300L	300	15	0.4	77	100	15
MCT4150300	MFL-300	300	12	0.4	77	100	20
MCT4160300	MFL-300L	300	15	0.4	77	100	15
MCT4170360	MFO-360	360	12	0.4	92	100	15
MCT4180360	MFO-360L	360	15	0.4	92	100	10
MCT4190360	MFL-360	360	12	0.4	92	100	15
MCT4200360	MFL-360L	360	15	0.4	92	100	10
MCT4210520	MFO-520	520	12	0.4	145	100	20
MCT4220520	MFO-520L	520	15	0.4	145	100	20
MCT4230520	MFL-520	520	12	0.4	145	100	20
MCT4240520	MFL-520L	520	15	0.4	145	100	20
MCT4250680	MFO-680	680	12	0.4	190	100	20
MCT4260680	MFO-680L	680	15	0.4	190	100	20
MCT4270680	MFL-680	680	12	0.4	190	100	20
MCT4280680	MFL-680L	680	15	0.4	190	100	20
MCT4290840	MFO-840	840	12	0.4	245	100	15
MCT4300840	MFO-840L	840	15	0.4	245	100	15
MCT4310840	MFL-840	840	12	0.4	245	100	15
MCT4300840	MFO-840L	840	15	0.4	245	100	15
MCT4331050	MFO-1050	1050	12	0.4	280	100	10
MCT4341050	MFO-1050L	1050	15	0.4	280	100	10
MCT4351050	MFL-1050	1050	12	0.4	280	100	10
MCT4341050	MFO-1050L	1050	15	0.4	280	100	10

SKETCHES:
millimeter

