

Fully Vinyl Insulated Disconnect

- Usage: connect wires, cables, electrical products
- Material: brass
- Tools required: tools clamp



ITEMS:

0.5~1.5mm² 22-16AWG I_{max}=10A

Catalog No	Model	Dimensions (mm)					NEMA TAB (mm)	isolated color	Quantity in bag	Quantity in carton (bag)
		L	d∅	D∅	B	W				
MWT11010408	FDFD1.25-187(5)	20.00	1.70	4	5	5.6	0.5x4.75	● red	100	120
MWT11010409	FDFD1.25-187(8)	20.00	1.70	4	5	5.6	0.8x4.75	● red	100	120
MWT11010410	FDFD1.25-250	21.50	1.70	4	6.6	7.4	0.8x6.35	● red	100	60

1.5~2.5mm² 16-14AWG I_{max}=15A

Catalog No	Model	Dimensions (mm)					NEMA TAB (mm)	isolated color	Quantity in bag	Quantity in carton (bag)
		L	d∅	D∅	B	W				
MWT11010411	FDFD2-187(5)	20.00	2.30	4.5	5	5.6	0.5x4.75	● blue	100	60
MWT11010412	FDFD2-187(8)	20.00	2.30	4.5	5	5.6	0.8x4.75	● blue	100	60
MWT11010413	FDFD2-250	21.50	2.30	4.5	6.6	7.4	0.8x6.35	● blue	100	60

4~6mm² 12-10AWG I_{max}=24A

Catalog No	Model	Dimensions (mm)					NEMA TAB (mm)	isolated color	Quantity in bag	Quantity in carton (bag)
		L	d∅	D∅	B	W				
MWT11010414	FDFD5.5-250	25.50	3.40	5.7	6.6	7.4	0.8x6.35	● yellow	100	120

SKETCHES:

mm

