

Insulated Bullet & Receptacle Disconnect female

- Usage: connect wires, cables, electrical products
- Material: brass
- Tools required: tools clamp



ITEMS:

0.5~1.5mm² 22-16AWG I_{max}=10A

Catalog No	Model	Dimensions (mm)						Thickness of material (mm)	isolated color	Quantity in bag	Quantity in carton (bag)
		L	H	d∅	D∅	F	b∅				
MWT90010404	FRD1.25-156	24.5	13	1.7	2.7	16	4	0.4	● red	100	96

1.5~2.5mm² 16-14AWG I_{max}=15A

Catalog No	Model	Dimensions (mm)						Thickness of material (mm)	isolated color	Quantity in bag	Quantity in carton (bag)
		L	H	d∅	D∅	F	b∅				
MWT90010405	FRD2-156	24.5	14	2.3	3.3	6.3	4	0.4	● blue	100	96
MWT90010406	FRD2-195	24.5	14	2.3	3.3	7	5	0.4	● blue	100	72

4~6mm² 12-10AWG I_{max}=24A

Catalog No	Model	Dimensions (mm)						Thickness of material (mm)	isolated color	Quantity in bag	Quantity in carton (bag)
		L	H	d∅	D∅	F	b∅				
MWT90010407	FRD5.5-195	29.5	14	3.4	4.5	7	5	0.4	● yellow	100	72

SKETCHES: mm

