

Insulated Bullet & Receptacle Disconnect male

- Usage: connect wires, cables, electrical products
- Material: brass
- Tools required: tools clamp



ITEMS:

0.5~1.5mm² 22-16AWG I_{max}=10A

Catalog No	Model	Dimensions (mm)						Thickness of material (mm)	isolated color	Quantity in bag	Quantity in carton (bag)
		L	H	d∅	D∅	F	b∅				
MWT90010400	MPD1.25-156	21	10	1.7	2.7	11	4	0.4	● red	100	240

1.5~2.5mm² 16-14AWG I_{max}=15A

Catalog No	Model	Dimensions (mm)						Thickness of material (mm)	isolated color	Quantity in bag	Quantity in carton (bag)
		L	H	d∅	D∅	F	b∅				
MWT90010401	MPD2-156	21	10	1.7	2.7	16	4	0.4	● blue	100	180
MWT90010402	MPD2-195	21	10	1.7	2.7	16	5	0.4	● blue	100	180

4~6mm² 12-10AWG I_{max}=24A

Catalog No	Model	Dimensions (mm)						Thickness of material (mm)	isolated color	Quantity in bag	Quantity in carton (bag)
		L	H	d∅	D∅	F	b∅				
MWT90010403	MPD5.5-195	25	14	3.4	4.5	11	5	0.4	● yellow	100	120

SKETCHES:
mm

