

# Insulated Female Disconnect

- Usage: connect wires, cables, electrical products
- Material: brass
- Tools required: tools clamp



## ITEMS:

0.5~1.5mm<sup>2</sup> 22-16AWG I<sub>max</sub>=10A

Catalog No	Model	Dimensions (mm)					Thickness of material (mm)	NEMA TAB (mm)	isolated color	Quantity in bag	Quantity in carton (bag)
		H	L	DØ	dØ	B					
MWT80010384	FDD1.25-110(5)	10	19.00	3.8	1.7	3.8	0.3	0.5x2.8	● red	100	240
MWT70010385	FDD1.25-110(8)	10	19.00	3.8	1.7	3.8	0.3	0.8x2.8	● red	100	240
MWT70010386	FDD1.25-187(5)	10	19.00	3.8	1.7	5.6	0.35	0.5x4.75	● red	100	240
MWT70010387	FDD1.25-187(8)	10	19.00	3.8	1.7	5.6	0.35	0.8x4.75	● red	100	240
MWT70010388	FDD1.25-205	10	20.00	3.8	1.7	6.5	0.35	0.5x5.2	● red	100	120
MWT70010389	FDD1.25-250	10	21.00	3.8	1.7	7.4	0.4	0.8x6.35	● red	100	120

1.5~2.5mm<sup>2</sup> 16-14AWG I<sub>max</sub>=15A

Catalog No	Model	Dimensions (mm)					Thickness of material (mm)	NEMA TAB (mm)	isolated color	Quantity in bag	Quantity in carton (bag)
		H	L	DØ	dØ	B					
MWT80010390	FDD2-110(5)	10	19.00	4.3	2.3	3.8	0.3	0.5x2.8	● blue	100	240
MWT80010391	FDD2-110(8)	10	19.00	4.3	2.3	3.8	0.3	0.8x2.8	● blue	100	240
MWT80010392	FDD2-187(5)	10	19.00	4.3	2.3	5.6	0.35	0.5x4.75	● blue	100	240
MWT80010393	FDD2-187(8)	10	19.00	4.3	2.3	5.6	0.35	0.8x4.75	● blue	100	240
MWT80010394	FDD2-205	10	20.00	4.3	2.3	6.5	0.35	0.5x5.2	● blue	100	120
MWT80010395	FDD2-250	10	21.00	4.3	2.3	7.4	0.4	0.8x6.35	● blue	100	120
MWT80010396	FDD2-312	10	23.00	4.3	2.3	9	0.4	0.8x8.0	● blue	100	120

4~6mm<sup>2</sup> 12-10AWG I<sub>max</sub>=24A

Catalog No	Model	Dimensions (mm)					Thickness of material (mm)	NEMA TAB (mm)	isolated color	Quantity in bag	Quantity in carton (bag)
		H	L	DØ	dØ	B					
MWT80010397	FDD5.5-250	14	25.00	5.7	3.4	7.4	0.4	0.5x6.35	● yellow	100	120
MWT80010398	FDD5.5-375	14	29.60	5.7	3.4	10.9	0.5	1.2x9.4	● yellow	100	120

SKETCHES:  
mm

