

Insulated Male Disconnect

- Usage: connect wires, cables, electrical products
- Material: brass
- Tools required: tools clamp



ITEMS:

0.5~1.5mm² 22-16AWG I_{max}=10A

Catalog No	Model	Dimensions (mm)					Thickness of material (mm)	NEMA TAB (mm)	isolated color	Quantity in bag	Quantity in carton (bag)
		H	L	DØ	dØ	B					
MWT70010376	MDD1.25-110(8)	10	17.70	4.3	1.7	2.8	0.8	0.8×2.8	● red	100	240
MWT70010377	MDD1.25-187(5)	10	20.00	4.3	1.7	4.75	0.5	0.5×4.75	● red	100	240
MWT70010378	MDD1.25-187(8)	10	18.50	4.3	1.7	4.75	0.8	0.8×4.75	● red	100	240
MWT70010379	MDD1.25-250	10	21.00	4.3	1.7	6.35	0.4	0.8×6.35	● red	100	240

1.5~2.5mm² 16-14AWG I_{max}=15A

Catalog No	Model	Dimensions (mm)					Thickness of material (mm)	NEMA TAB (mm)	isolated color	Quantity in bag	Quantity in carton (bag)
		H	L	DØ	dØ	B					
MWT70010380	MDD2-187(5)	10	20.00	4.3	2.3	4.75	0.5	0.5×4.75	● blue	100	240
MWT70010381	MDD2-187(8)	10	18.50	4.3	2.3	4.75	0.8	0.8×4.75	● blue	100	240
MWT70010382	MDD2-250	10	21.00	4.3	2.3	6.35	0.4	0.8×6.35	● blue	100	240

4~6mm² 12-10AWG I_{max}=24A

Catalog No	Model	Dimensions (mm)					Thickness of material (mm)	NEMA TAB (mm)	isolated color	Quantity in bag	Quantity in carton (bag)
		H	L	DØ	dØ	B					
MWT70010383	MDD5.5-250	14	25.00	5.7	3.4	6.35	0.4	0.8×6.35	● yellow	100	120

SKETCHES: mm

