

Insulated Ring Terminals

- Usage: connect wires, cables, electrical products
- Material: copper
- Tools required: tools clamp



ITEMS:

0.5~1.5mm² 22-16AWG I_{max}=19A

Catalog No	Model	Dimensions (mm)					Screw Diameter (mm)	US System of Bolt	isolated color	Quantity in bag	Quantity in carton (bag)
		DØ	H	F	L	B					
MWT00010069	RV1.25-3	3.4	4.8	4.95	12.6	5.7	3.2	#4	● red	100	240
MWT00010070	RVS1.25-3.5	3.4	4.8	4.95	12.6	5.7	3.7	#6	● red	100	240
MWT00010071	RVM1.25-3.5	3.4	4.8	6.3	14.4	6.6	3.7	#6	● red	100	240
MWT00010072	RVL1.25-3.5	3.4	4.8	7	15.8	8	3.7	#6	● red	100	240
MWT00010073	RVS1.25-4	3.4	4.8	6.3	14.4	6.6	4.3	#8	● red	100	240
MWT00010074	RVL1.25-4	3.4	4.8	7	15.8	8	4.3	#8	● red	100	240
MWT00010075	RV1.25-5	3.4	4.8	7	15.8	8	5.3	#10	● red	100	240
MWT00010076	RV1.25-6	3.4	4.8	11.1	21.8	11.6	6.5	1/4	● red	100	180
MWT00010077	RV1.25-8	3.4	4.8	11.1	21.8	11.6	8.4	5/16	● red	100	180
MWT00010078	RV1.25-10	3.4	4.8	13.6	25.5	13.6	10.5	3/8	● red	100	120

1.5~2.5mm² 16-14AWG I_{max}=27A

Catalog No	Model	Dimensions (mm)					Screw Diameter (mm)	US System of Bolt	isolated color	Quantity in bag	Quantity in carton (bag)
		DØ	H	F	L	B					
MWT00010079	RV2-3	4.9	10	4.3	17.8	6.6	3.2	#4	● blue	100	240
MWT00010080	RVS2-3.5	4.9	10	4.3	17.8	6.6	3.7	#6	● blue	100	240
MWT00010081	RVM2-3.5	4.9	10	7	21	6.6	3.7	#6	● blue	100	180
MWT00010082	RVL2-3.5	4.9	10	7.75	22.5	8.5	3.7	#6	● blue	100	180
MWT00010083	RVS2-4	4.9	10	7	21	6.6	4.3	#8	● blue	100	180
MWT00010084	RVL2-4	4.9	10	7.75	22.5	8.5	4.3	#8	● blue	100	180
MWT00010085	RVS2-5	4.9	10	7.75	22.5	8.5	5.3	#10	● blue	100	180
MWT00010086	RVL2-5	4.9	10	7.25	22.5	9.5	5.3	#10	● blue	100	120
MWT00010087	RV2-6	4.9	10	11	27.6	12	6.5	1/4	● blue	100	144
MWT00010088	RV2-8	4.9	10	11	27.6	12	8.4	5/16	● blue	100	120
MWT00010089	RV2-10	4.9	10	13.9	30.2	13.6	10.5	3/8	● blue	100	120



2.5~4mm² 14-12AWG I_{max}=37A

Catalog No	Model	Dimensions (mm)					Screw Diameter (mm)	US System of Bolt	isolated color	Quantity in bag	Quantity in carton (bag)
		DØ	H	F	L	B					
MWT00010090	RV3.5-4	6.2	12.5	7.7	24.5	8	4.3	#8	● black	100	120
MWT00010091	RVS3.5-5	6.2	12.5	7.7	24.5	8	5.3	#10	● black	100	120
MWT00010092	RVL3.5-5	6.2	12.5	7.7	27.9	12	5.3	#10	● black	100	96
MWT00010093	RV3.5-6	6.2	12.5	7.7	27.9	12	6.5	1/4	● black	100	96

4~6mm² 12-10AWG I_{max}=48A

Catalog No	Model	Dimensions (mm)					Screw Diameter (mm)	US System of Bolt	isolated color	Quantity in bag	Quantity in carton (bag)
		DØ	H	F	L	B					
MWT00010094	RV5.5-3.5	6.7	12.5	5.9	21.4	7.2	3.7	#6	● yellow	100	96
MWT00010095	RVS5.5-4	6.7	12.5	5.9	21.5	7.2	4.3	#8	● yellow	100	120
MWT00010096	RVL5.5-4	6.7	12.5	8.3	25.5	9.5	4.3	#8	● yellow	100	72
MWT00010097	RV5.5-5	6.7	12.5	8.3	25.5	9.5	5.3	#10	● yellow	100	96
MWT00010098	RV5.5-6	6.7	12.5	13	31.5	12	6.5	1/4	● yellow	100	72
MWT00010099	RV5.5-8	6.7	12.5	13.7	33.7	15	8.4	5/16	● yellow	100	72
MWT00010100	RV5.5-10	6.7	12.5	13.7	33.7	15	10.5	3/8	● yellow	100	60
MWT00010101	RV5.5-12	6.7	12.5	16	38.1	19.2	13	1/2	● yellow	100	60

SKETCHES:
mm

