

# Insulated Spade Terminals

- Usage: connect wires, cables, electrical products
- Material: copper
- Tools required: tools clamp



## ITEMS:

0.5~1.5mm<sup>2</sup> 22-16AWG I<sub>max</sub>=19A

Catalog No	Model	Dimensions (mm)						Screw Diameter (mm)	US System of Bolt	isolated color	Quantity in bag	Quantity in carton (bag)
		DØ	H	F	L	B	d2					
MWT10010001	SV1.25-3	4.3	10	6.5	21.2	5.7	3.2	#4	● red	100	240	
MWT10010002	SVS1.25-3.5	4.3	10	6.5	21.2	5.7	3.7	#6	● red	100	240	
MWT10010003	SVL1.25-3.5	4.3	10	6.5	21.2	6.4	3.7	#6	● red	100	240	
MWT10010004	SVS1.25-4	4.3	10	6.5	21.2	6.4	4.3	#8	● red	100	240	
MWT10010005	SVM1.25-4	4.3	10	6.5	21.2	7.2	4.3	#8	● red	100	240	
MWT10010006	SVL1.25-4	4.3	10	6.5	21.2	8.1	4.3	#8	● red	100	240	
MWT10010007	SVS1.25-5	4.3	10	6.5	21.2	8.1	5.3	#10	● red	100	240	
MWT10010008	SVL1.25-5	4.3	10	6.5	21.2	9.5	5.3	#10	● red	100	180	
MWT10010009	SVS1.25-6	4.3	10	6.5	21.2	9.5	6.5	1/4	● red	100	180	
MWT10010010	SVL1.25-6	4.3	10	11	21.2	12	6.5	1/4	● red	100	120	

1.5~2.5mm<sup>2</sup> 16-14AWG I<sub>max</sub>=27A

Catalog No	Model	Dimensions (mm)						Screw Diameter (mm)	US System of Bolt	isolated color	Quantity in bag	Quantity in carton (bag)
		DØ	H	F	L	B	d2					
MWT10010011	SV2-3	4.9	10	6.5	21.2	5.7	3.2	#4	● blue	100	240	
MWT10010012	SVS2-3.5	4.9	10	6.5	21.2	5.7	3.7	#6	● blue	100	240	
MWT10010013	SVL2-3.5	4.9	10	6.5	21.2	6.4	3.7	#6	● blue	100	240	
MWT10010014	SVS2-4	4.9	10	6.5	21.2	6	4.3	#8	● blue	100	180	
MWT10010015	SVM2-4	4.9	10	6.5	21.2	7.2	4.3	#8	● blue	100	180	
MWT10010016	SVL2-4	4.9	10	6.5	21.2	8.1	4.3	#8	● blue	100	180	
MWT10010017	SVS2-5	4.9	10	6.5	21.2	8.1	5.3	#10	● blue	100	180	
MWT10010018	SVL2-5	4.9	10	6.5	21.2	9.5	5.3	#10	● blue	100	180	
MWT10010019	SVS2-6	4.9	10	6.5	21.2	9.5	6.5	1/4	● blue	100	180	
MWT10010020	SVL2-6	4.9	10	11	21.2	12	6.5	1/4	● blue	100	120	



2.5~4mm<sup>2</sup> 14-12AWG I<sub>max</sub>=37A

Catalog No	Model	Dimensions (mm)					Screw Diameter (mm)	US System of Bolt	isolated color	Quantity in bag	Quantity in carton (bag)
		DØ	H	F	L	B					
MWT10010021	SV3.5-4	6.2	12.5	7	24.8	8	4.3	#8	● black	100	120
MWT10010022	SV3.5-5	6.2	12.5	7	24.8	8	5.3	#10	● black	100	120
MWT10010023	SV3.5-6	6.2	12.5	12.1	28	12	6.5	1/4	● black	100	60

4~6mm<sup>2</sup> 12-10AWG I<sub>max</sub>=48A

Catalog No	Model	Dimensions (mm)					Screw Diameter (mm)	US System of Bolt	isolated color	Quantity in bag	Quantity in carton (bag)
		DØ	H	F	L	B					
MWT10010024	SV5.5-3.5	6.7	12.5	7.5	25.2	8.3	3.7	#6	● yellow	100	120
MWT10010025	SVS5.5-4	6.7	12.5	7.5	25.2	8.3	4.3	#8	● yellow	100	96
MWT10010026	SVL5.5-4	6.7	12.5	7.5	23.9	9	4.3	#8	● yellow	100	96
MWT10010027	SV5.5-5	6.7	12.5	7.5	23.9	9	5.3	#10	● yellow	100	96
MWT10010028	SVS5.5-6	6.7	12.5	7.5	23.9	9	6.5	1/4	● yellow	100	96
MWT10010029	SVL5.5-6	6.7	12.5	12	31.2	12	6.5	1/4	● yellow	100	72
MWT10010030	SV5.5-8	6.7	12.5	11.5	30	14	8.4	5/16	● yellow	100	72

SKETCHES:  
mm

